# Chesapeake Bay Program
# Tidal Monitoring Network Design And
# Criteria Assessment Methodology

Richard Batiuk

Associate Director for Science
U.S. Environmental Protection Agency
Chesapeake Bay Program Office
Annapolis, Maryland

**Chesapeake Bay Program**
*A Watershed Partnership*

# Overview of Presentation

- Spatial/Temporal Scale of Criteria Assessment

- Tidal Monitoring Network Design

- Shallow-Water Monitoring Effort

- Rationale for Criteria Assessment Methodology

- Analytical Framework for Criteria Assessment

# Objective

Define a set of tools that can be used to support criteria attainment decisions based on:

1. Magnitude of Criteria Exceedence

2. Spatial and Temporal Extent of Criteria Exceedance

3. Statistical Significance of Criteria Exceedence

# The Challenge

- **Magnitude**

- **Duration**

- **Frequency**

- **Space**

- **Time**

National Research Council. 2001. *Assessing the TMDL Approach to Water Quality Management*

# Spatial/Temporal Scales of Criteria Assessment

# Designated Uses for Chesapeake Bay

A. Cross Section of Chesapeake Bay or Tidal Tributary

Shallow Water

Open Water

Deep Water

Deep Channel

B. Oblique View of the "Chesapeake Bay" and its Tidal Tributaries

Migratory Finfish Spawning and Nursery Habitat

Open Water Habitat

Shallow Water Habitat

Deep Water

Deep Channel

# Application of Water-Quality Criteria

|  | Dissolved Oxygen | Chlorophyll a | Water Clarity |
|---|---|---|---|
| Migratory Spawning and Nursery | X | X |  |
| Shallow Water | X | X | X |
| Open Water | X | X |  |
| Deep Water | X |  |  |
| Deep Channel | X |  |  |

# Spatial Extent of Tidal Monitoring



CBP Monitoring Segmentation

Fixed-Station
Water-Quality Monitoring
Network

in Relation to the

Open Water, Deep Water
and Deep Channel
Designated Uses

Fixed-Station
Water-Quality
Monitoring Network

in Relation to the

Migratory and
Spawning
Designated Use

# Fixed-Station

# Water-Quality Monitoring

# Network

## in Relation to the

## Shallow Water

## Designated Use

# Interpretation Of Fixed-Station Data



CHESAPEAKE BAY
Parameter Computed by Interpolation
Dissolved Oxygen - Jun 1, 1985-Sep 30, 1994

# Tidal Water-Quality Monitoring Network Design

# Objectives of Tidal Monitoring

A. Characterization, Status

      - Water-Quality Criteria
      - Nutrient Reduction Goals
      - Biological and Ecological Indicators

B. Temporal Changes - Long-Term Trends

C. Tidal Water-Quality Modeling

D. Understanding of Processes Related to the Attainment of Water-Quality Criteria and Other Restoration Goals

# Tidal Monitoring Framework

| Objective: Characterization, Status - Criteria Attainment | | | |
|---|---|---|---|
| | Dissolved Oxygen | Chlorophyll a | Clarity |
| Migratory Spawning and Nursery | Fixed-Station Network – Spatially enhance where needed  Buoy System – Strategically located | Fixed-Station Network - To cover open-water areas | |
| Shallow Water | Probability-Based Network – Base-line spatial extent  DataFlow – Episodic / Strategic Basis  Buoy System – Strategically located | Probability-Based Network - To cover shallow-water areas  DataFlow – Episodic / Strategic Basis | Probability-Based Network – Base-line spatial extent  DataFlow – Episodic / Strategic Basis |
| Open Water | Fixed-Station Network – Spatially enhance where needed  Buoy System – Strategically located | Remote Sensing – Map the spatial extent of blooms | |
| Deep Water | Current Fixed-Station Network  Buoy System – Strategically located | | |
| Deep Channel | Current Fixed-Station Network  Buoy System – Strategically located | | |


# Shallow Water Monitoring

# Rationale for Shallow-Water Monitoring Design

- Little Prior Knowledge

- Can be Extremely Dynamic

- High Spatial Variability

- Critical Habitat

- Most Fish Kills

# Buoy Data for Continuous DO Measurements
## Severn River at Ben Oaks

Fish Kills Attributed to Low Dissolved Oxygen 1987 - 2001

Patopsco River

Magothy River

Ben Oaks

Severn River

South River

Fish Kills Attributed to Low Dissolved Oxygen
Chesapeake Bay, Maryland
Upper Western Shore Area
1987-2001

Source: Maryalnd Department of Environment
Fish Kill Investigation Section, Fish Kill Data base

# **Medium Tributary**



- Existing Fixed Stations

- Spatially Intensive Data Collection

- Continuous Buoys

# Components of Shallow-Water Monitoring Design

- Fixed-Station Continuous – Temporally Intensive

    - **Dissolved oxygen**
    - **Fluorescence**
    - **Turbidity**
    - **Water temperature**
    - **Salinity**
    - **pH**

- Water-Quality Mapping – Spatially Intensive

    - **Dissolved oxygen**
    - **Fluorescence**
    - **Turbidity**
    - **Water temperature**
    - **Salinity**

# Continuous Underway Monitoring

# Value of Water Quality Mapping for Identifying SAV Habitat

# Current Shallow-Water Monitoring Plans

- Current Funding Allows for Shallow-Water Monitoring in 16 (out of ~ 100) Segments

- Selected Segments Include 10 in MD, 6 in VA
  - Maryland – Severn, Magothy, Patuxent, Bush, Gunpowder, Middle, Chicamacomico and Chester
  - Virginia – York, Mattaponi, Pamunkey

- At the Current Rate, A Full Assessment Will Not Be Completed Until 2020

# **Rationale for Criteria Assessment Approach**

# Monitoring for Criteria Assessment
## Conceptual Example 1 - One Fixed Station per Segment

Fixed-Station Network

Actual Spatial Distribution of Parameter

Assessment Based on 10% Rule

# Monitoring for Criteria Assessment
## Conceptual Example 2 - Multiple Fixed Stations per Segment

Fixed-Station Network

Actual Spatial Distribution of Parameter

Assessment Based on 10% Rule

# Monitoring for Criteria Assessment
## Conceptual Example 3 – Use of Stations Outside of Segment



Fixed-Station Network

Actual Spatial Distribution of Parameter

Assessment Based on 10% Rule

# Monitoring for Criteria Assessment
## Conceptual Example 4 – Use of New Technologies

Fixed-Station Network

Actual Spatial Distribution of Parameter

Assessment Based on 10% Rule

# Analytical Approach for Criteria Assessment

# Approach for Defining Attainment of Criteria and Designated Uses

1. Develop an analytical tool that uses available data to account for spatial and temporal variability in criteria exceedence.

2. Analytical tool should be able to incorporate and benefit from different types of data including data collected using new technologies.

3. Analytical tool should provide a precise rule for deciding if a given segment is attaining its designated use.

# Steps for Developing a CFD

**Step 1: Interpolate the Bay water quality monitoring data for each sampling event (e.g., cruise)**

✏ Station



Surface Chl-a Concentration

SumChl
- No Data
- 0 - 5
- 5.1 - 10
- 10.1 - 15
- 15.1 - 20
- 20.1 - 40
- 40.1 - 60
- 60.1 - 80

**Step 2. Evaluate interpolated WQ monitoring data interpolator cell by cell using the appropriate criterion value**

# Step 3. Identify the cells in a CBP segment / designated use area that exceed the criteria for each sampling event



Exceedance Layer

Meets Criteria
Exceeds Criteria

# Step 4. Repeat Step 3 for each sampling event in assessment period ...



Exceedance Layers

March 1999

April 1999

May 1999

June 1999

March 2000

Apr 2000

May 2000

Assessment Period

**Step 5. Compile the measures of % area (%volume) exceeding the criteria. This quantifies the SPATIAL EXTENT of the exceedences in a segment for each sampling event.**

**Example Assessment Over A Three Year Assessment Period**

| Month | % Area (%Volume) Exceeding |
|---|---|
| Mar-98 | 72.0000 |
| Apr-98 | 55.0000 |
| May-98 | 65.0000 |
| Jun-98 | 75.0000 |
| Mar-99 | 49.0000 |
| Apr-99 | 34.0000 |
| May-99 | 67.0000 |
| Jun-99 | 25.0000 |
| Mar-00 | 20.0000 |
| Apr-00 | 39.0000 |
| May-00 | 35.0000 |
| Jun-00 | 50.0000 |

# Step 6. Sort and rank the measures of % area/volume of criteria exceedence

**Example Assessment Over A Three Year Assessment Period**

| Month | % Area (%Volume) Exceeding | Rank |
|-------|----------------------------|------|
| Jun-98 | 75.0000 | 1 |
| Mar-98 | 72.0000 | 2 |
| May-99 | 67.0000 | 3 |
| May-98 | 65.0000 | 4 |
| Apr-98 | 55.0000 | 5 |
| Jun-00 | 50.0000 | 6 |
| Mar-99 | 49.0000 | 7 |
| Apr-00 | 39.0000 | 8 |
| May-00 | 35.0000 | 9 |
| Apr-99 | 34.0000 | 10 |
| Jun-99 | 25.0000 | 11 |
| Mar-00 | 20.0000 | 12 |

## Step 6. Calculate the cumulative probability values based on the ranks

| Month | % Area (%Volume) Exceeding | Rank | Cumulative Probability (Rank/n+1) |
|---|---|---|---|
| | 100.0000 | | 0.0000 |
| Jun-98 | 75.0000 | 1 | 7.6923 |
| Mar-98 | 72.0000 | 2 | 15.3846 |
| May-99 | 67.0000 | 3 | 23.0769 |
| May-98 | 65.0000 | 4 | 30.7692 |
| Apr-98 | 55.0000 | 5 | 38.4615 |
| Jun-00 | 50.0000 | 6 | 46.1538 |
| Mar-99 | 49.0000 | 7 | 53.8462 |
| Apr-00 | 39.0000 | 8 | 61.5385 |
| May-00 | 35.0000 | 9 | 69.2308 |
| Apr-99 | 34.0000 | 10 | 76.9231 |
| Jun-99 | 25.0000 | 11 | 84.6154 |
| Mar-00 | 20.0000 | 12 | 92.3077 |
| | 0.0000 | | 100.0000 |

# Step 7. Plot the % area in exceedence vs. cumulative probability over time

## Example Assessment Over A Three Year Assessment Period



April 2000 X=39%, Y=62%

May 1998
X = 65%, Y = 31%

%Time the Given % Area/ Volume is in exceedence

% Area/Volume in Exceedence

# Use of CFD's for Characterizing Spatial and Temporal Extent of Criteria Exceedence

Can we go beyond 10% towards something more reflective/protective of the living resources?

Three Reference Curve Options

# Deep Water Dissolved Oxygen Criteria Reference Curve

# Definition of Attainment

# Definition of Attainment:
## Any Excursion Above the Reference Curve

Definition of Attainment
Kolmogorov-Smirnov Test

# Map Magnitude of Exceedence

Express criteria exceedence in terms of percent of criteria value evaluated over the assessment period and illustrated spatially



1998-2000 Summer Season Median Surface Chlorophyll-a Concentrations

*Expressed as Percent of Criteria Value*

**Percent of Criteria Value**

- No Data
- < 50
- 50 - 75
- 75 – 100
- 100 – 150
- 150 – 200
- 200 – 250
- 250 – 300
- > 300

# Tools For Defining Attainment



Magnitude of Exceedence

Spatial and Temporal Extent of Exceedence

Statistical Significance

Statistical

Test